


## FPL STANDARD FIXED FORKS PALLET LIFTER

### PRODUCT FEATURES:

- Converts overhead crane to lift truck.
- Counter balanced to hang level when empty.
- Maintenance free.
- Allows for ease of loading/unloading in not easily accessible areas.
- Complies with ASME standards.



### SPECIFICATIONS


Model Number	Capacity (tons)	Dimensions (inches)										Weight (lbs.)
		Forks			W	E	Bail			J*	HR	
		L	M	N			A	B	C			
FPL136	1	36	2	2	25	18	1	6	5	48	57-1/2	292
FPL142	1	42	2	2	25	21	1	6	5	48	57-1/2	310
FPL148	1	48	2	2	25	24	1	6	5	48	58-1/2	371
FPL1536	1-1/2	36	3	2	25	18	1	6	5	48	58-1/2	388
FPL1542	1-1/2	42	3	2	25	21	1	6	5	48	58-1/2	432
FPL1548	1-1/2	48	3	2	25	24	1	6	5	48	58-1/2	459
FPL236	2	36	3	2	25	18	1	6	5	48	59-1/2	448
FPL242	2	42	4	2	25	21	1	6	5	48	59-1/2	536
FPL248	2	48	4	2	25	24	1	6	5	48	59-1/2	627
FPL342	3	42	4-1/2	2-1/2	25	21	1-1/2	6-1/8	7	48	61-1/2	766
FPL348	3	48	4-1/2	2-1/2	27	24	1-1/2	6-1/8	7	48	61-1/2	823
FPL354	3	54	4-1/2	2-1/2	30	27	1-1/2	6-1/8	7	48	61-1/2	969
FPL448	4	48	5	3	27	24	1-1/2	6-1/8	7	48	63-1/2	1176
FPL460	4	60	5	3	30	30	1-1/2	6-1/8	7	60	75-1/2	1393
FPL548	5	48	5	3	30	24	1-1/2	6-1/8	7	48	63-1/2	1193
FPL560	5	60	4-1/2	2-1/2	38	30	1-1/2	8-1/8	7	60	75-1/2	1403

\* We recommend an additional 3"-4" clearance above the load for ease of loading and unloading the lifter.

## HPL HEAVY DUTY FIXED FORKS PALLET LIFTER

### PRODUCT FEATURES:

- Double frame design for heavy capacities.
- Counter balanced to hang level when empty.
- Maintenance free.
- Complies with ASME standards.



### SPECIFICATIONS

Model Number	Capacity (tons)	Dimensions (inches)										Weight (lbs.)
		Forks			W	E	Bail			J*	HR	
		L	M	N			A	B	C			
HPL7548	7-1/2	48	6	2-1/2	30	24	2	5	9	48	65	1910
HPL7560	7-1/2	60	10	3	38	30	2	5	9	60	79	2400
HPL1048	10	48	10	3	30	24	2	5	9	48	69	1950
HPL1060	10	60	10	3	38	30	2	5	9	60	81	3100
HPL1548	15	48	10	3	38	24	2	6	12	60	84	2250
HPL1560	15	60	10	3	38	30	2	6	12	60	75	3800
HPL2060	20	60	7	4	38	30	2-1/4	6	12	60	88	4300
HPL2072	20	72	8-1/4	4	44	36	2-1/4	6	12	60	88	4850

\* We recommend an additional 3"-4" clearance above the load for ease of loading and unloading the lifter.

