


# APL STANDARD ADJUSTABLE FORKS PALLET LIFTER

## PRODUCT FEATURES:

- Converts overhead crane into lift truck.
- Pry bar adjustable forks to handle multiple pallet sizes.
- Counter balanced to hang level when empty.
- Complies with ASME standards.



## SPECIFICATIONS


Model Number	Capacity (tons)	Dimensions (inches)											Weight (lbs.)
		Forks			W			Bail			J*	HR	
		L	M	N	Min.	Max.	E	A	B	C			
APL136	1	36	2	2	16	38	18	1	3	5	48	58	670
APL142	1	42	2	2	16	38	21	1	3	5	48	58	760
APL148	1	48	2	2	16	38	24	1	3	5	48	59	780
APL1536	1-1/2	36	3	2	16	38	18	1	3	5	48	59	845
APL1542	1-1/2	42	3	2	16	38	21	1	3	5	48	59	900
APL1548	1-1/2	48	3	2	16	38	24	1	3	5	48	60	950
APL236	2	36	3	2	16	38	18	1	3	5	48	60	980
APL242	2	42	4	2	16	38	21	1	3	5	48	60	1060
APL248	2	48	4	2	16	38	24	1	3	5	48	59-1/2	1080
APL342	3	42	4-1/2	2-1/2	16	38	21	1-1/2	4	7	48	61-1/2	1250
APL348	3	48	4-1/2	2-1/2	16	38	24	1-1/2	4	7	48	61-1/2	1368
APL354	3	54	4-1/2	2-1/2	16	38	27	1-1/2	4	7	48	63	2005
APL448	4	48	5	3	19	38	24	1-1/2	4	7	48	64	1600
APL460	4	60	5	3	19	38	30	1-1/2	4	7	60	76	2240
APL548	5	48	5	3	19	38	24	1-1/2	4	7	48	65	1865
APL560	5	60	4-1/2	2-1/2	19	38	30	1-1/2	4	7	60	77	2190

\* We recommend an additional 3"-4" clearance above the load for ease of loading and unloading the lifter.

# HAPL HEAVY DUTY ADJUSTABLE FORKS PALLET LIFTER

## PRODUCT FEATURES:

- Forged forks gives ease of adjustment.
- Smaller fork sizes gained using forged forks.
- Double frame design for heavy capacities.
- Complies with ASME standards.



## SPECIFICATIONS

Model Number	Capacity (tons)	Dimensions (inches)											Weight (lbs.)
		Forks			W			Bail			J*	HR	
		L	M	N	Min.	Max.	E	A	B	C			
HAPL7548	7-1/2	48	6	2-1/2	20	48	24	2	5	9	48	64-1/2	2400
HAPL7560	7-1/2	60	6	3	20	48	30	2	5	9	60	77-1/2	3300
HAPL7572	7-1/2	72	6	3	20	48	36	2	5	9	60	80	3750
HAPL1048	10	48	6	3	20	48	24	2	5	9	48	68	2900
HAPL1060	10	60	6	3	20	48	30	2	5	9	60	79-1/2	4300
HAPL1072	10	72	7	3	20	48	36	2	5	9	60	79-1/2	4900
HAPL12548	12-1/2	48	6	3	20	48	24	2	6	12	48	82	3900
HAPL12560	12-1/2	60	6	3	20	42	30	2	6	12	60	82	4700
HAPL12572	12-1/2	72	7	3-1/2	20	38	36	2	6	12	60	82	5500

\* We recommend an additional 3"-4" clearance above the load for ease of loading and unloading the lifter.

