

FARM CLEVISES



General Purpose Clevis–AgWorks™

Formed from low carbon steel. Painted black.



Part Number	UPC	Body Size	Std. Pack	WLL (lbs.)	Approx. Wt. Ea. (lbs.)
65958	65958-0	3/4	5	10,000	3.0

Working Load Limit (WLL) 10,000 lbs.

Twist Clevis–AgWorks™

Formed from low carbon steel. Painted black.



Part Number	UPC	Body Size	Std. Pack	WLL (Lbs.)	Approx. Wt. Ea. (lbs.)
65620	65620-6	5/8	5	6,000	1.4
65621	65621-3	3/4	5	12,000	2.4
65622	65622-0	7/8	5	16,000	3.0
65623	65623-7	7/8 Long	5	16,000	3.6
65624	65624-4	15/16	5	20,000	4.2
65625	65625-1	1	5	25,000	6.0

• Supplied with Tee Handle clevis pin

Straight Clevis–AgWorks™

Formed from low carbon steel. Painted black.



Part Number	UPC	Body Size	Std. Pack	WLL (Lbs.)	Approx. Wt. Ea. (lbs.)
65990	65990-0	5/8	5	6,000	1.4
65991	65991-7	3/4	5	12,000	2.4
65992	65992-4	7/8	5	16,000	3.0
65993	65993-1	7/8 Long	5	16,000	3.6
65994	65994-8	15/16	5	20,000	4.2
65995	65995-5	1	5	25,000	6.0

• Supplied with Tee Handle clevis pin

Utility Clevis–AgWorks™

Formed from low carbon steel. Painted black.



Part Number	UPC	Body Size	Std. Pack	WLL (Lbs.)	Approx. Wt. Ea. (lbs.)
65640	65640-4	1/4	10	1,000	.10
65641	65641-1	5/16	10	1,500	.20
65642	65642-8	3/8	10	2,000	.30
65643	65643-5	7/16	10	3,000	.40
65644	65644-2	1/2	10	4,000	.60
65645	65645-9	5/8	10	6,500	1.2

Screw Pin Clevis–AgWorks™

Medium carbon steel, quenched and tempered. Hot forged. Painted black.



Part Number	UPC	Body Size	Std. Pack	WLL (Lbs.)	Approx. Wt. Ea. (lbs.)
65630	65630-5	1/4	10	1,000	.25
65631	65631-2	5/16	10	1,500	.35
65632	65632-9	3/8	10	2,000	.50
65633	65633-6	7/16	10	3,000	.55
65634	65634-3	1/2	10	4,000	.75
65635	65635-0	5/8	10	6,500	1.3
65636	65636-7	3/4	10	9,500	2.2
65637	65637-4	7/8	10	12,000	3.5
65638	65638-1	1	10	17,000	5.0



WARNING

Improper use or care of shackles/clevises can result in bodily injury or property damage.

To Avoid Injury: • Do not exceed working load limit. • Do not shock or impact load. • Do not side load—center line of load must coincide with the center line of shackle/clevis. • Do not replace pin or bolt with other than original equipment parts. • Inspect before use for wear, deformation, and pin engagement.

Replacement Tee Handle Clevis Pins–AgWorks™

Medium carbon steel, quenched and tempered. Clevis Pins fit clevises listed below.



Part Number	UPC#	For Clevis Numbers	Diameter (In.)	Usable Length (In.)	Standard Pack	Approx. Wt. Ea. (Lbs.)
65700	65700-5	65990 / 65620	1/2	2 1/4	5	0.4
65701	65701-2	65621 / 65991	5/8	3 1/8	5	0.5
65702	65702-9	65622 / 65992 65623 / 65993	3/4	3 1/4	5	0.7
65703	65703-6	65624 / 65994	7/8	3 3/8	5	1.2
65704	65704-3	65625 / 65995	1	3 3/4	5	1.5

1-800-756-6656