



CBTP (Plain)
1/4 to 5 Ton



CBTG (Geared)
1 to 5 Ton

CBT Model Trolleys

- Rated loads from 1/4 to 5 Ton (Metric Rated). In plain and geared models.
- Trolley easily adjusts to fit any beam flange within range of adjustment, up to an 8.7" flange width.
- Dual Tread Wheels fit either tapered or flat beam flange within range of adjustment. Wheels include permanently lubricated, shielded ball bearings for long life and low maintenance.
- Low Rolling Effort — Geared models have standard 6-foot hand chain drop. Other hand chain drops available.
- Wrap-around side plates provide additional security to increase operator safety and act as bumpers to protect wheels.
- Universal Hanging Clevis accepts most hook mounted hoists.
- Rugged — Designed to provide superior performance and long, efficient service.
- Economical — Excellent low cost choice for manual and powered hoists.
- Lifetime Warranty

SPECIFICATIONS

CBT Plain & Geared Trolleys • 1/4 - 5 Tons

Model Number**	Capacity* (Ton)	Standard Beam Height (In.)	I-Beam Width (In.)	Minimum Radius Curve (In.)	Wheel Tread Diameter (In.)	Weight (Lbs.)
CBTP-0025	1/4	4 - 24	2.0 - 8.7	27	2.36	19
CBTP-0050	1/2	4 - 24	2.0 - 8.7	27	2.36	19
CBTP(G)-0100	1	5 - 24	2.3 - 8.7	36	2.36	26
CBTP(G)-0150	1 1/2	6 - 24	2.3 - 8.7	45	3.15	46
CBTP(G)-0200	2	6 - 24	2.3 - 8.7	45	3.15	46
CBTP(G)-0300	3	8 - 24	3.0 - 8.7	55	4.41	86
CBTP(G)-0500	5	10 - 24	3.5 - 8.7	70	4.92	130

* Metric Rated

** When ordering specify "P" for plain trolley or "G" for geared trolley