

LMTP & LMTG Trolleys

- Rated loads from 8-16 tons in plain and geared models. Geared trolleys have standard 7-foot hand chain drop.
- Designed for heavy-duty industrial applications.
- Hanging clevis accepts all Little Mule hook-mounted hoists. Steel equalizing pin can be used to suspend hoist for low headroom applications.
- Adjustable — Fits a wide range of beam sizes.
- Wrap-around side plates act as trolley guards and bumpers for added security and wheel protection.
- Ball Tread Wheels — Cast iron wheels (8-16 Ton models) fit any tapered or flat beam flange within range of adjustment. Each wheel has two lifetime lubricated, sealed tapered roller bearings for long life and low maintenance.
- Options — Wide flange and patented track models available. Spark resistant units available in 4 to 8 Ton models.



LMTP
(Plain)
8 - 16 Ton



LMTG
(Geared)
8 - 16 Ton

SPECIFICATIONS

LMTP / LMTG Plain & Geared Trolleys • 8 - 16 Tons

Model Number*	Capacity		Beam Height (In.)	I-Beam Flange Width (In.)	Minimum Radius Curve (In.)	Net Weight	
	Lbs.	Tons				Plain (Lbs.)	Geared (Lbs.)
LMTP(G)-16000	16000	8	10 - 24	4.66 - 7.00	72	255	295
LMTP(G)-20000	20000	10	10 - 24	4.66 - 7.00	72	274	310
LMTP(G)-24000	24000	12	10 - 24	4.66 - 7.00	72	278	320
LMTP(G)-32000	32000	16	18 - 24	6.00 - 8.00	96	800	840

* When ordering specify "P" for plain trolley or "G" for geared trolley.

Note: LMTP & LMTG trolleys up to 40 ton capacity available upon request - consult factory

BC Beam Clamps

- Rated loads from 1-10 Ton.
- Reduced flange stress — Special clamp jaw design distributes load away from flange edge.
- Threaded mechanism fits securely on a wide range of flange widths and beam sizes.
- Low headroom provided by built-in suspension bar.

SPECIFICATIONS BC Beam Clamps • 1 - 10 Tons

Model Number*	Capacity		Flange Width (In.)	Weight (Lbs.)
	Lbs.	Tons		
BC-1	2000	1	3 - 9	9
BC-2	4000	2	3 - 9	13
BC-3	6000	3	3.2 - 12.6	18
BC-5	10000	5	3.6 - 12.2	22
BC-10	20000	10	3.6 - 12.6	32



1 - 10 Ton