


CHESTER HOIST

WORM DRIVE HOIST
DATA SHEET E-202AS

CAPACITY 7 1/2 TON

LOW HEADROOM
MOTORIZED TROLLEY - T

SINGLE HOOK MONORAIL
2-PART DOUBLE



ALL DIMENSIONS IN INCHES

MODEL NUMBER	CAPACITY (lbs.)	SPEED (fpm)	LIFT (ft.)	REEVING	MOTOR (hp)	C	L	ST'D. I-BEAM		APPROX. WT. (lbs.)
								SIZE	CLEAR*	
WDMT-151S	15000	20	15	2PD-7/16E	15 @ 1200	50 5/8	17 1/2	7-24	1/2	2400
WDMT-152S	15000	20	25	2PD-7/16E	15 @ 1200	59 5/8	22	7-24	1/2	2500
WDMT-152AS	15000	20	35	2PD-7/16E	15 @ 1200	65 5/8	25	7-24	1/2	2600
WDMT-152BS	15000	20	50	2PD-7/16E	15 @ 1200	77 5/8	31	7-24	1/2	2700
WDMT-152CS	15000	20	65	2PD-7/16E	15 @ 1200	89 5/8	37	7-24	1/2	2800

* CLEARANCE BASED ON MAX. "S" BEAM SIZE 24" @ 100 LBS.
TROLLEYS FOR OTHER I-BEAMS AND PATENTED TRACKS ARE AVAILABLE.
MAXIMUM BEAM FLANGE WIDTH 7 1/2 INCHES.
NOTE: WHEN USING SCREW TYPE LIMIT SWITCH ADD 1 INCH TO HEADROOM.